



Model No.	Part No.	Speed & Torque 90 psig Air Pressure*					Overall Length		Weight		Head Dimensions				Standard Square Drive Size	Tube Capacities*		Chuck Size †
		Free Speed	Maximum Torque		Minimum Torque						Side to Center	Height Less Square Drive		In.		mm		
		RPM	Ft. lbs.	Nm	Ft. Lbs.	Nm	In.	mm	Lbs.	Kg	In.	mm	In.	mm				

Reversible – Roll Throttle


 1753-R-190	8405420	190	140	190	70	95	20.1	530	13	5.8	1.1	28	2.6	65	5/8	2.5	63.5	3/4
 1752-R-90	8405421	90	305	410	150	200	21.7	550	14.75	6.7	1.5	37	2.75	70	3/4	4	101.5	3/4-1

Reversible – Lever Throttle

 1752-L-90	8405425	90	305	410	150	200	21.7	550	14.75	6.7	1.5	37	2.6	65	3/4	4	101.5	3/4-1
---	---------	----	-----	-----	-----	-----	------	-----	-------	-----	-----	----	-----	----	-----	---	-------	-------

† See page 31 for chuck size chart.

* Varies depending on tube gauge and tube sheet thickness.

 Refer to page 5 for description of Rapid Select.

STANDARD EQUIPMENT

Air Inlet: 1/2" NPT

Minimum hose size: 1/2"

Splined torque reaction plate and reaction bar included.